

Smart axes and related method

INS. a1
The invention relates to a displacement unit and related method, as described in the preambles of claims 1 and 39.

INS. a2
From DE 41 06 689 A1 a method for controlling a processing machine is known, in particular an assembly machine and similar processing machine. The latter comprises a plurality of workpiece carriers, which are moved past workstations on a moving track or work line in transport direction. The latter are designed respectively for at least one prespecified procedure and are controlled at least partly by an electronic control unit. Each workstation has its own electronic control unit, which is equivalent to the control units of other workstations, whereby the control unit of each workstation only cooperates with the immediately following and/or immediately preceding workstation via a data and control line. At the first workstation an electronic protocol is established for each workpiece carrier, which in addition to an identification identifying or characterising said workpiece carrier contains the work to be performed in transport direction at subsequent workstations. Said protocol is then sent according to the work stages via a data line from the control unit of the preceding workstation to the control unit of the subsequent workstation. The disadvantage of this design is that the individual workstations comprise various different components according to the work to be performed, which excludes the serial manufacture of the various components. In this way it is not possible to produce such an assembly machine using standardised individual components, which is disadvantageous for the manufacturing costs of such an assembly machine. A further disadvantage is that once a production process has been commenced it is not possible to intervene to correct an erroneous protocol for example. Furthermore, the central monitoring or direct programming of a particular workstation is not possible for example with an additional simulation procedure.

The objective of the present invention is to create a displacement unit which is composed of separate standardised components and can be integrated as a standardised component itself into a complete system and thus a modular structure - for example an assembly line - can be created.

09485947

a The objective of the invention is achieved by means of the features described in the characterising part of claim ⁴⁴~~1~~. The surprising advantage is that the control unit is connected directly to the displacement unit and thus expensive installation of wiring can be avoided on the one hand and specific functions of the adjusting unit can be preset without external programming. In this way for example the expense of programming can be reduced considerably and it is possible to produce the transport devices in series as standard units without the special manufacture of parts designed for specific uses being necessary.

⁴⁶~~2~~ A development according to claim ⁴⁶~~2~~ is advantageous, whereby it is possible to combine various different designs of switching modules with any control modules.

a An embodiment according to claim ⁴⁷~~3~~ is also advantageous, whereby information can be gathered centrally from all different parts of the displacement unit.

a A development according to claim ⁴⁸~~4~~ has proved to be advantageous, which permits the rapid and simple manufacture of a connection.

a A further embodiment is described in claim ⁴⁹~~5~~ in which information can be transmitted from a central area to the various units of a displacement unit.

a If the development according to claim ⁵⁰~~6~~ is realised, a rapid and simple line connection can be achieved in relation to outgoing information.

a An embodiment according to claim ⁵¹~~7~~ is also advantageous, in which program sequences can be determined directly in the control unit.

a The developments according to claims ^{52 and 53}~~8 and 9~~ are advantageous, in which the control unit is small and a rapid transfer of information is ensured.

a An embodiment according to claim ⁵⁴~~10~~ has the advantage that the control unit is independent of an external power supply and thus the smooth operation of the displacement unit is ensured.

0945547.012.00

a A development according to claim ⁵⁵~~11~~ is also possible, in which in a simple manner the device can be adjusted to different situations and thus a high degree of flexibility is achieved.

a An embodiment according to claims ^{56 to 59}~~12 to 15~~ has the advantage that the transfer of power and information is performed by robust elements, whereby the maintenance costs of such displacement units is reduced.

a A development according to claim ⁶⁰~~16~~ is also advantageous, whereby the modular construction of the displacement unit or an assembly system composed of displacement units is improved, which leads in particular to a reduction in assembly costs.

a An embodiment according to claim ⁶¹~~17~~ has proved to be advantageous, whereby the connections for the control unit are designed for a modular structure of the displacement unit or assembly unit composed therefrom.

An embodiment according to claim 18 has the advantage that short line lengths and thereby short switching and pulse times can be achieved.

a A development according to claim ⁶²~~19~~ is also possible by means of which the assembly of the switching modules can be performed rapidly and any arrangement of the switching modules in the displacement unit is possible.

a A development according to claim ⁶³~~20~~ is advantageous, whereby each individual switching module can be controlled and monitored individually.

a The embodiment described in claim ⁶⁴~~21~~ means that the volume of a pneumatic cylinder can be changed as a result of which the latter can be used flexibly and adapted to different conditions.

a A development according to claim ⁶⁵~~22~~ is advantageous, whereby a precise monitoring and thereby control of the displacement unit is made possible.

09465947 "0142100

- a An embodiment according to claims ^{67 67}~~23~~ and ~~24~~ is also advantageous, whereby a precise positioning of a component of the displacement unit is possible, without the mechanical loading on braking a moved part being too great
- a The developments according to claims ^{68 70}~~25~~ to ~~27~~ permit a dialogue between an operator and the control unit, preferably directly at the displacement unit.
- a A variant according to claim ⁷¹~~28~~ is also advantageous, whereby assembly is facilitated and the manufacturing costs are thus considerably reduced.
- a A development according to claim ⁷²~~29~~ is also advantageous, whereby expensive cabling and piping is avoided and the assembly costs can be further reduced.
- a A development according to claims ^{73 74}~~30~~ and ~~31~~ is advantageous, which reduces the likelihood of disruption on transmitting power or control signals and the number of individual parts in a displacement unit is reduced thus, further improving the modular structure.
- a A development according to claim ⁷⁵~~32~~ is also possible, permitting the simple assembly of the signalling and/or monitoring members on the displacement unit and in addition achieving a flexible arrangement thereof.
- a The design described in claim ⁷⁶~~33~~ has the advantage that information is sent via a central line and thus the cost of wiring is further reduced.
- a A design according to claim ⁷⁷~~34~~ is advantageous, in which an individual signalling and/or monitoring member can be monitored and/or programmed, whereby the possible use of such displacement units is extended by the thus achieved flexibility.
- a An embodiment according to claim ⁷⁸~~35~~ is also advantageous, by means of which the manual entering of data is avoided, and data is picked up automatically, thereby reducing the pulse times of an assembly system comprising several displacement units.

0945547 042100

79
36, by

80
37 i

81
38

827

83
40 is

84

a An embodiment according to claim ~~42~~⁸⁵ is a

a Finally, a development according to claim 43 is

These show:

Fig. 2 a section of the displacement unit 1 of the invention, in particular a control unit, in perspective view;

Fig. 4 a further embodiment of the displacement unit of the invention, in cross section, in plan view;

Fig. 6 a further embodiment of the displacement unit of the invention, in front elevation;

Fig. 8 a circuit diagram of the control unit of the displacement unit of the invention;

Fig. 9 a time-motion diagram of the displacement unit of the invention;

Fig. 10 a flowchart of the method of the invention for operating the displacement unit according to the invention;

Fig. 11 a flowchart of the method for operating the displacement unit of the invention;

Fig. 12 a further embodiment of the displacement unit according to the invention, in cross section, in plan view;

Fig. 13 the displacement unit of the invention, in cross section along the lines XIII-XIII of Fig. 12.

First of all it should be noted that in the descriptions of the various embodiments the same parts are given the same reference numbers or component names, whereby the disclosures contained throughout the description can be applied to the same parts with the same reference numbers or the same component names. Also the details relating to position, such as e.g. top, bottom, side etc. relate to the Figure being described at the time and should be transposed to a new position when the position has changed. Furthermore, individual features of the various embodiments shown can represent independent solutions according to the invention.

In Fig. 1 a displacement unit 1 for example for supply, manipulation, joining or control systems of an assembly system for mounting parts 2 is shown. The latter comprises components 3, 4 that can be displaced relative to one another using a drive unit 5, for example by means of compressed air, electricity or hydraulic fluid. Furthermore, the displacement unit 1 comprises at least one guiding device 6 for at least one of the components 3, 4. The displacement unit 1 also comprises a control unit 7, whereby at least one member 8 of the control unit 7 processing logic information and/or bus information and/or a command is integrated into the drive unit 5 and/or into at least one of the components 3, 4 and/or is mounted on one of the components 3; 4.

The control unit 7 comprises at least one control module 9 and/or one or more switching modules 10 allocated to the control module 9. At least one switching module 10 of the control unit 7 is designed for example as a pneumatic valve 11. It can however also be designed as a relay or as a contactor. The control unit 7, in particular the switching modules 10 are con-

At least one mounting part 2 is located on a transport device 18, which in the present embodiment comprises a drive and/or guiding device 19 and workpiece carrier 20. The drive and/or guiding device 19 comprises for example drive axes 21, which run perpendicular to the transport device and to a central axis 22 of the pneumatic cylinder 13. A drive wheel 23 is arranged on the drive axis 21 and secured thereto and can be made for example of plastic or metal with a plastic coating. Spaced apart from the drive wheel 23 at a distance 24 measured parallel to the drive axis 21 is a guiding wheel 25 which is secured immobily not with the drive axis 21 for example. The guiding wheel 25, in particular a surface 26 thereof is pressed for example by means of elastic force against a flank surface 27 of the workpiece carrier 20 running parallel thereto and at right angles to the drive axis 21, whereby an inner spacing 28 of a recess 29 of the workpiece carrier 20 parallel to the distance 24 corresponds to the distance 24 plus a double wheel width 30.

The pneumatic cylinder 13 has a piston 36 forming the component 4, which has a piston surface 37 at right angles to the central axis 22, beyond which a piston rod 38 projects. In an end

region of the piston rod 38 facing away from the piston surface 37 the former comprises in the present embodiment a pressure piece 39, which is screwed onto the piston rod 38 for example, in particular onto a threaded section 40 thereof. In this way the displacement unit 1 in the present embodiment acts as a joining system, in particular as a pressing device for assembly parts.

On an outer surface 41 of the cylindrical pipe 15 is the control unit 7, which is mounted for example on a console 42 connected detachably or non-detachably to the outer surface 41. The switching modules 10 are preferably connected detachably to the console 42 and are formed for example by a 4/2-way-valve 43, two restrictor return valves 44, 45 and two 3/2-way-valves 46, 47. The switching modules 10 comprise for example electrically operated drives 48, which are connected by control lines 49 to the control module 9 illustrated by dashed lines. Of course, it is possible to design the control lines 49 not only as free, i.e. flexible, lines but to integrate them into an electric distribution bar or cable channel. The switching modules 10 are connected according to their switching function for example by lines 50, in particular pneumatic pipes 51. The control unit 7, in particular the control module 9 has inputs 52, for example for signals and/or commands of a central control unit and/or the signalling and/or monitoring members 16 and/or for signals and/or commands of an additional control unit 7 of further displacement units 1 and/or external input and/or output devices and/or drive units 5 and/or power and/or switching modules 10, whereby the inputs 52 are connected for example by single point plugs with single lines, which can also be connected non-detachably to the inputs 52.

The inputs 52 can also be connected by at least one multipoint plug with at least one multipoint line and/or by a bus connector plug 53 to a central connecting line. The control unit 7, in particular the control module 9 can also comprise outputs 54 which permit the output of signals and/or commands to the central control unit and/or the switching modules 10. Furthermore, outputs 54 can be used for example for signals and/or commands to the signalling and/or monitoring members 16 and/or control units 7 of additional displacement units 1 and/or to external input and/or output devices and/or to drive units 5 and/or for power. The output of signals and/or commands can be performed by means of the bus connector plug 53 which also forms an input 52.

On an upper side 62 running perpendicular to the end face 59 and surrounded by the length 56 and the width 57, openings 60 are also provided, preferably for the switching modules 10. Thus for example for the 4/2-way-valve 43 adjacent to the end face 59 on the upper side 62 there are four openings 60 connected to corresponding openings 63 in the switching modules 10. The channels 61 are formed for example by an air inlet channel 64, an air outlet channel 65 and two connecting channels 66, 67. An opening 63 of the 4/2-way-valve 43 is connected to a channel 61 for example by a plug. Spaced apart from the 4/2-way-valve 43 in the opposite direction to the end face 59 is the 3/2-way-valve 46. The latter also comprises openings 63, one of which is connected preferably detachably with the connecting channel 66, and in which the restrictor return valve 44 is arranged. Facing away from the upper side 62 of the pneumatic distribution bar 55 and parallel to the latter the 3/2-way-valve 46 is delimited by an upper side 68, which comprises two openings 63, one opening 63 comprising for example a sound damper 69, whereas the other opening 63 is connected to the pneumatic cylinder 13 shown in Fig. 1. The latter openings 63 can however also be arranged on the underside 70 of the 3/2-way-valve 46 facing the upper side 62 and away from the upper side 68, as a result of which in the pneumatic distribution bar 55 further channels 61 would be necessary.

Spaced apart from the 3/2-way-valve 46 in opposite direction to the 4/2-way-valve 43 is the 3/2-way-valve 47, which is connected by an opening 63 by an opening 60 arranged in the upper side 62 of the distribution bar 55 with the connecting channel 67. Out of the opening 63 a restrictor return valve 45 extends for example inside the 3/2-way-valve 47. There are also openings 63 on the upper side 68 of the 3/2-way-valve 47, whereby one opening 63 has a sound damper 69, and the other opening 63 is connected to the pneumatic cylinder 13 shown

in Fig. 1. A configuration of this kind or connection of switching modules 10 is preferably used for the end position damping of pneumatic cylinder 13 to be explained in more detail.

Of course in this way any arrangement of switching modules 10 and thereby the realisation of various controls can be achieved. Accordingly the number of channels 61 arranged in the pneumatic distribution bar 55 and the switching modules 10 arranged on the pneumatic distribution bar 55 can be varied as desired. It is also possible to integrate the switching modules 10 into the pneumatic distribution bar 55 and not, as shown by way of example, to arrange them detachably or non-detachably on the upper side 62. In addition, the switching modules 10 can also be arranged on or in the cylindrical pipe 15 instead of being arranged on a pneumatic distribution bar 55. In particular at least one component 3; 4 can comprise a pneumatic distribution bar 55.

In Fig. 3 a development of the control unit 7 is shown in perspective view. The latter comprises for example – as described for Fig. 2 – a pneumatic distribution bar 55 which comprises channels 61 and on the upper side 62 of which several switching modules 10 are arranged. The switching modules 10 comprise drives 71 which are connected detachably or non-detachably with the switching module 10 or with an electric distribution bus bar 72 preferably by plugs 74 designed as coupling devices 73. In the present embodiment the electric distribution bus bar 72 is a part of the control unit 7. It is however also possible to form a flexible connection between the electric distribution bus bars 72 and the control unit 7. Also the electric distribution bus bar 72 should not only be understood to be a rigid line connection, but can also be formed by flexible single lines preferably running into a housing.

The control unit 7, in particular the control module 9 comprises in the present embodiment at least one display element 75, which is designed for example as a display 76 with text, number display, light-emitting diodes and/or acoustic information elements. In addition, the control unit 7 can comprise an input device 77, preferably in the form of a keyboard 78. The latter can however also be formed by a touch screen which combines the input device 77 with the display 76. The display element 75 together with the input device 77 forms an input and/or output device 79. The electric distribution bus bars 72 and/or the control unit 7 comprise on an end side face 80 for example a multipoint plug 81 designed as an input 52 and/or output 54. It is also possible to use the bus connector plug 53 described in Fig. 1.

The flanges 85 are a component of a piston body 86, which has a rectangular cross section for example in a plane perpendicular to the central axis 22. The flanges 85 and the piston plates 84 are adjusted in outline to the cross section of the cylindrical inner chamber 83 and are designed to be circular for example, i.e. concentric to the central axis 22. An outer surface 87 delimiting the piston body 86 and parallel to the central axis 22 is used for mounting a slide 88 which passes through a slot-shaped longitudinal opening 89 arranged in the cylindrical pipe 15. The slide 88 comprises a pneumatic distribution bar 55, which is secured detachably or non-detachably to an upper side 90 of the slide 88 perpendicular to the outer surface 87. The slide 88 has a height 91 measured parallel to the outer surface 87 which spaces the upper side 90 from an underside 92 of the slide 88 parallel thereto. The slot height 93 of the longitudinal opening 89 measured parallel to the slide height 91 is greater than the slide height 91 plus the bar height 58 of the pneumatic distribution bar 55. On the upper side 62 of the distribution bar 55 or the electric distribution bus bars 72, which can also be arranged on the upper side 90 of the slide 88, are the switching modules 10. From the switching modules 10 lines 50 run to connection openings 82 of an additional displacement unit 1, which is also designed for example as a pneumatic cylinder 13, but with a piston rod 38.

The slide 88 is delimited in opposite direction to the outer surface 87 of the piston body 86 and thus the component 4 by an end face 94, which has a mechanical interface 95 for additional displacement units 1 and/or assembly and/or processing devices and/or for power and/or for control units 7. In place of lines 50 said mechanical interface 95 can be designed so that the end face 94 or the end face 59 of the pneumatic distribution bar 55 comprises not shown openings which correspond with also not shown openings in the other displacement

unit 1. It is also possible instead of a separate pneumatic distribution bar 55 to design the slide 88 to have integrated channels 61.

On an inner end face 96 of the slide 88 or the pneumatic distribution bar 55 and/or the electric distribution bus bars 72 running parallel to the end face 94 and opposite the latter are inputs 52 and/or outputs 54 which are combined in the present embodiment in the form of a bus-line 97. It is also possible however, instead of the bus line 97 to use a multipoint line or single lines. The bus line 97 can be flexible or rigid and runs as far as the piston plate 84 which faces the control unit 7 for the pneumatic cylinder 13 without a piston rod. In said piston plate 84 there are inputs 52 and/or outputs 54 which are designed for example as coupling devices 98. From said coupling devices 98 up to the adjacent closing element 14 of the pneumatic cylinder 13 without a piston rod extend one or more control lines 49 and/or one or more lines 50 which are designed to be adjustable in length for example in the form of a spiral.

On an outer surface 99 of the closing element 14 facing away from the piston 36 are coupling devices 98, which are allocated to the control lines 49 and/or lines 50.

The control line 7 is also arranged on the outer surface 99. The latter also comprises a display 76 and/or a keyboard 78. The control unit 7, in particular the control module 9 has inputs 52 and/or outputs 54, which also can be designed as coupling devices 98 and are used for the transmission of signals and/or commands for example to a central control unit. This transmission is however not necessarily possible only by means of lines 50 or control lines 49, but can also be performed for example optically by means of lasers or for example by means of infrared or ultrasound. From the control module 9 extends an ASIC bus line 100 for example, which supplies the switching modules 10 or the signalling and/or monitoring members 16 with power and/or data or conveys data from the latter. The ASIC bus line 100 is preferably bipolar. Via an interface 101 and/or via an evaluation unit 102 the signals and/or commands originating from the control module 9 and/or the central control unit and transmitted by the ASIC bus line 100 are transmitted to an electric distribution bus bar 72 which is arranged in a guiding device 103.

The guiding device 103 is preferably arranged in the cylindrical pipe 15 and extends for example at least over a portion of a length 104 of the drive unit 5. It is thus designed so that it

The cylindrical pipe 15 also comprises connection openings 82 projecting from the outer surface 41 in the direction of the inner chamber of the cylinder 83. Symmetrically about the central plane 106, a bore distance apart 113 channels 61 run in the cylindrical pipe 15, in particular an air inlet channel 64 and an air outlet channel 65. From the latter connecting channels 114 extend up to the groove 108 and run at right angles to the outer surface 41.

The guiding device 103 also forms a bar-shaped securing device 118 for the signalling and/or monitoring members 16. These can also comprise control modules 9. It is also possible not to integrate the guiding device 103 into the drive unit 5, i.e. into the cylindrical pipe 15, but to design it as a separate component, which is secured detachably or non-detachably to the drive unit 5, in particular the cylindrical pipe 15. In this way the guiding device 103 can comprise several connection openings arranged at prespecified distances in the direction of the length 104, at least one of which corresponds with connection openings 82 arranged in the cylindri-

cal pipe 15, i.e. in the drive unit 5. In this way it is possible to design the guiding device 103 for a modular structure of the displacement unit 1.

In Fig. 6 a further embodiment of a displacement unit 1 according to the invention is shown. The latter comprises components 3, 4 that are adjustable relative to one another, whereby component 4 is arranged by means of a guiding device 6 designed for example as a linear guide 119 on the preferably frame-shaped component 3. The guiding device 6 can however also be designed as a rotary and/or gear guide for example or as a sliding track. The frame-shaped component 3 for example has two parallel connecting elements 120, which are spaced apart by longitudinal elements 121 running at right angles and parallel to one another. The connecting elements 120 are used for mounting securing devices 122 which are formed for example by a damping device 123, in particular a shock absorber 124. In this way the component 4 is restricted in at least one direction of movement on the component 3. Signalling and/or monitoring members 16 are also arranged in the connecting elements 120, which are designed for example in the form of capacitive proximity switches 17.

The guiding device 6 is designed for example as a ball bush guide whereby the component 4 has at least one ball bush 125, in which a guide shaft 126 is inserted, which is arranged securely on the component 3. A longitudinal element 121 comprises for example the drive unit 5 which in the present embodiment is also designed as a pneumatic cylinder 13.

Said pneumatic cylinder 13 is designed as a linear cylinder and comprises the slide 88 on which component 4 is secured. The latter comprises in turn the interface 95, on which for example a not shown additional displacement unit 1 can be arranged and in the region of which also not shown inputs 52 and/or outputs 54 of a control unit 7 can be arranged, which can be line connected by plug connections to a control unit 7 of a not shown additional displacement unit 1. Integrated into the drive unit 5 or the component 4 is the pneumatic distribution bar 55 and/or the electric distribution bus bar 72 with the control module 9. The electric distribution bus bar 72 is connected by dot-dash shown control lines 49 to signalling and/or monitoring members 16 and the pneumatic distribution bar 55 via lines 50, for example pneumatic pipes 51 to the switching modules 10.

As shown for example in the jointly described Figs. 7 to 9, the control module 9 is in the form of a microprocessor 127 for example, which is connected by conductors 128 forming control lines 49 to an interface 129 forming an input 52 and/or output 54. The latter comprises an integrated or, as shown, an external evaluation unit 130 which is also connected to the microprocessor 127. In addition, a memory 131 for saving, in particular individual movements, and an input 52 and/or output 54 designed as an external interface 129 for external input and/or output devices 79 are connected to the microprocessor 127. In addition the microprocessor 127 can also be connected to a driver 132 which is arranged between outputs 54 and the microprocessor 127 and to a D/A converter 133 which is arranged between inputs 52, in particular for measuring members and/or signalling and/or monitoring members 16 and the microprocessor 127. The microprocessor 127 is designed so that it detects one or more of the following functions in parallel or in series:

- initialisation mode
- control mode
- learning mode
- monitoring mode

Of course, it is possible to provide a separate microprocessor 127 for each of these functions to perform these functions using a conventional control or perform them in a central control unit 134.

The initialisation mode is used so that on forming the connection between the control module 9 and the control unit 134, the basic parameters of the control module 9 or the displacement unit 1 are transmitted. The latter can for example be transmitted in the form of a program which makes the potential reference values of the displacement units 1, in particular the pneumatic cylinder 13, appear on an external input and/or output device 79 or on a screen of the control unit 134. Said potential reference values, such as example displacements in x and y direction, speeds and forces can therefore be stored in the memory 131. The operator can now determine the actual, i.e. current reference values, for example the displacement, the acceleration, the deceleration of the piston 36 of the pneumatic cylinder 13, according to the individual movement situation. This can be performed for example in such a way that by means of the input and/or output device 79 or by means of the control unit 134, the potential

reference values can be shown as variables, which can be provided by the operator with the corresponding current reference values. If the current reference value entered by the operator exceeds the stored potential reference value, a warning can be sent to the operator for example.

Such an initialisation of a displacement unit 1 can however also be performed by means of a data glove and simulation of the displacement unit 1 directly at the control module 9. In this case the operator with the data glove executes the movement to be performed directly in the relevant assembly station.. The displacement unit 1 performs these movements of the data glove preferably simultaneously and transmits the values detected by measuring members and/or the signalling and/or monitoring members 16, for example x and y components, to the microprocessor 127 and/or to the control unit 134, whereby the data glove is connected couplably by inputs 52 and/or outputs 54 to the control unit 7 and/or the control unit 134, and the movement data conveyed to the latter. The latter calculate from this a function of the movement and store it as a program. In particular by using a data glove as an input and/or output device 79 the expense of programming can be considerably reduced and the displacement unit 1 can be used variably accordingly. The x and y components can however also be detected by a local positioning system similar to the GPS. Thus for example when producing not shown different mounting parts 2 on an assembly device for each individual mounting part 2 and each individual displacement unit 1 a corresponding program can be developed rapidly and saved. The input and/or output device 79 can however also be designed as a keyboard, a reading device for chipcards, magnetic cards, CDs, diskettes or tapes.

The other control modules 9 or displacement units 1 can be initialised in the same way. On using a bus line system the control module 9 following the already initialised control module 9 can be connected to the former via the not shown bus line 97. In this case the potential reference values are sent to the central control unit 134 avoiding the preceding control module 9. The operator can now also determine the actual reference values for this additional control module 9, which can be stored in the control unit 134 or in the memory 131 as data or in program form. In this manner for each individual control module 9 the corresponding handling program can be provided.

The control mode is carried out as follows.

In this case, as already described above, the operator by means of the control unit 134 or an external input and/or output device 79 can instruct the microprocessor 127 of the control module 9 of this other displacement unit 1, to enter a signal received by a signalling and/or monitoring member 16, for example a position of the pneumatic cylinder 13 via the interface 129 to a control module 9 of a displacement unit 1 addressed into the bus line 136, whereby

this signal reaches the interface 129 of the control module 9 of the displacement unit 1 and is fed into the microprocessor 127 of this control module 9 where it is used as a starting pulse for the program for this displacement unit 1 determined by the operator after the initialisation mode in the memory 131 of the control module 9 or in the central control unit 134.

With the arrival of the start pulse in the microprocessor 127 its program begins to run. In this case by means of the driver 132, if there is one, one or more switching modules 10 are charged by one or more control lines 49, so that for example a coil designed as a drive 48 of the switching modules 10 is flowed through with current and a valve body is moved by means of magnetic force. In this way for example by means of the connection opening 82 of the pneumatic cylinder 13 shown in Fig. 4 the latter is charged with compressed air and operates for example at constant speed. It is also possible however instead of conventional pneumatic valves 11 to use servovalves and thus vary the speed of the piston 36.

If the piston 36 now reaches a position which can be detected by means of the measuring member and/or the signalling and/or monitoring member 16 shown in Fig. 4 and/or prespecified in the program of the microprocessor 127, a pulse arrives via a control line 49 to the microprocessor 127, which sends a corresponding signal to the switching module 10, i.e. to the drive 48 of a pneumatic valve 11, and for example ends the air supply to the pneumatic cylinder 13 and stops its movement. Of course, however the evaluation of sensors 137 designed as signalling and/or monitoring members 16 can also be performed in the control unit 134 and the drive or charging of individual actuators 138 of a displacement unit 1 can be performed directly via the central bus line 136. In addition, the switching and control procedures should not be understood to be restrictive and only represent a simple example of a control module 9. Furthermore, data can be transmitted between the control unit 7 and control unit 134 and/or from the individual components of the control unit 7 to the latter optically by means of lasers or for example by means of infrared or ultrasound.

As already explained the control module 9 also has a learning mode. In this case, as already shown in the control mode, for example a position to be reached by the piston 36, i.e. a reference value in the program of the microprocessor 127 designed as logic element 139 is predetermined and detected for example by means of a measuring member, in particular a displacement measuring device.

Once the piston 36 reaches this position the corresponding pulse of a displacement measuring device forming a signalling and/or monitoring member 16 is evaluated in the microprocessor 127, and the required pulse is sent to the switching module 10, which stops the supply of power to the drive unit 5. Due to the kinematic energy of the piston 36 however, despite ending the air supply, the piston 36 may move beyond the given position, which can affect the precision of positioning the displacement unit 1.

By means of the displacement measuring device the actual position, i.e. the actual value of the displacement unit 1, in particular the stopped piston 36 is detected, and sent to the microprocessor 127 and/or the central control unit 134, where the actual value is compared with the reference value and the difference between the reference position and the actual position of the piston 36 is determined. After determining the difference the microprocessor 127 sends a pulse for opening a switching module 10, whereby the piston 36 is moved back by the difference for example restricted, and thus the exact position is reached, i.e. the actual value is adjusted to the reference value. This difference is also used for the next displacement cycle, in order to actuate the switching module 10 not just when reaching the reference position, but earlier by the calculated difference. This means that the actual value is defined as the reference value which represents an optimised time value for example with respect to cycle time, wear, vibration etc. A learning mode of this kind is advantageous in particular for increasing the acceleration of the piston 36 and a corresponding damping, i.e. slowing down of the piston 36. The advantage of such a learning function is in particular that on using servovalves the pistons 36 of the pneumatic cylinder 13 are accelerated or slowed down, and in this way there is a change in the kinematic energy of the piston, which makes the deceleration of the piston more difficult to an exact position.

A further example of the learning mode can on using corresponding sensors 137, in particular microsensors, reduce the loading and thereby the wear of the displacement unit. Thus for example, as shown in Fig. 1, on the tool carrier 20, in particular on its upper side 31 a vibration sensor designed as a signalling and/or monitoring member 16 can be provided, which transmits its data wirelessly or by line to the control module 9 and/or to the control unit 134. A vibration sensor and/or force sensor of this kind can however also be arranged on the displacement unit 1 for example on component 3 and/or component 4.

If for example after the initialisation mode the first cycle of the displacement unit 1 is performed and as shown in Fig. 1 for example, a gripper with a mounting part 2 drives too „hard“ on the tool carrier 20 or a mount 32 for the mounting part 2, the vibration sensor transmits the value of the vibration to the control module 9 and/or the control unit 134. The latter evaluate the measurement value and on exceeding a specific predeterminable target value, for example by means of calculating algorithms such as fuzzy logic, neuronal networks or genetic algorithms, calculate a new end position of the gripper, which on reaching the mounting part 2 is no longer placed „so hard“ into the mount, which is achieved preferably by the end position damping described below. The relative number of cycles between two consecutive adjustments of the positions of the components 3, 4 can be used to determine a maintenance plan. In this way it is possible on the basis of the predeterminable reference value to determine an optimum drive curve of the displacement unit 1 and to control the switching modules 10 accordingly.

It is also possible however to detect wear by measuring pressure and thus establish maintenance prognoses. Thus for example on initialisation the pressure in the air inlet line of the pneumatic cylinder 13 is determined by a pressure sensor and saved in the memory 131. The actual pressures are detected cyclically. Due to wear, for example in the region of the piston 36 and the cylindrical pipe 15, or the linear guide 119 designed as a guiding device 6 and illustrated in Fig. 6 the sliding friction is reduced, which results in a reduction of frictional forces and thereby directly to a reduction in pressure. This drop in pressure thus signals the degree of wear of the elements concerned, and can, as already described, be used as parameters for the modes of the displacement unit 1.

By means of the also provided monitoring mode for example an exact maintenance and up-keeping of the displacement unit 1 can be performed. The microprocessor 127 counts for example the absolute number of performed cycles and the relative cycle number between two consecutive corrections of the parameters on the basis of the learning mode. If the relative cycle number drops so far that it falls below a predeterminable minimum cycle number the microprocessor 127 sends a repair signal either directly to the control unit 134 or via the external interface 129 to external input and/or output devices 79. The repair signal is set in a relation to the absolute cycle number and a maintenance plan for the future can be developed therefrom.

Of course, the wear can also be determined directly for example by surface roughness measurements and/or by continual measuring of the objects, for example the piston 36 or the sealing rings. Mainly in the areas of control and learning mode specific displacement modes for the displacement unit 1 such as a for example „normal drive“, „slow drive“ or „rapid drive“ can be predetermined by positioning paths and speed profiles 140.

The functions of the displacement unit 1 are now explained with reference to a control shown in Fig. 8 for variable speeds and end position damping of a piston 36 in a predeterminable position.

The starting point here is the available displacement time of a displacement unit 1 resulting from the cycle time of an assembly system, in particular a double acting pneumatic cylinder 13. The latter should be 70 ms for example. As illustrated better in Fig. 9 the speed profile 140 is formed therefrom. The pneumatic cylinder 13 is charged with compressed air on one side 142 at the time point and/or at position 141. The compressed air comes from a central or decentral compressed air supply 143, which is connected to an electrically operated 4/2 valve 144 formed as a switching module 10. The electrically operated 4/2-way-valve 144, for example the drive 145 designed as a coil is connected by a control line 49 and the driver 132 to the microprocessor 127, which via the interface 129, the evaluation unit 130 and the bus line 136 receives the starting signal from the control unit 134 or a control module 9 of a different displacement unit 1.

By means of this starting signal the 4/2-way-valve 144 is switched and a line 146 put under pressure. In this case a restrictor return valve 147 designed as a switching module 10 is released in flow direction to the pneumatic cylinder 13 and the compressed air reaches an electrically operated 3/2-way-valve 148 unrestrictedly. A drive 149 of this valve is connected by a separate control line 49 or via the control line 49 of the 4/2-way-valve 144 to the microprocessor 127 and is inactivated on the advance of the piston 36, so that a free passage of the compressed air is provided to side 142.

At the same time (as the time point or position 141) with the starting pulse at the 4/2-way-valve 144 a pulse is sent via a control line 49 to a further 3/2-way-valve 150, for example just by microprocessor 127 and not by the control unit 134, which is connected to the side 151 of

At the same time at position 156 by the microprocessor 127 a pulse is sent to the drive 149 of the first 3/2-way-valve 148 and activates the latter, as a result of which the side 142 is completely deaerated by a sound damper 152. The piston 36 now moves at maximum speed from position 156 to position 158. On reaching position 158 the pulse, i.e. the tension on the drive 149 of the first 3/2-way-valve 148 is removed, as a result of which the latter is returned by spring force into its position of rest, and frees the path in the direction of the first restrictor return valve 147, whereby the compressed air emerging from side 142 is restricted and the piston 36 is braked. Both in position 141 and in position 156 – as shown in Fig. 6 – securing devices 122 for example in the form of switchable end stops can be arranged, which themselves can act as signalling and/or monitoring members 16 or comprise additional signalling and/or monitoring members 16. If one is arranged at position 141, for example a pulse is sent via a separate control line 49 or a central connecting line 135 to the microprocessor 127, which conveys this signal via the evaluation unit 130 and the interface 129 to the control unit 134 and/or processes its into a pulse, in which it ends the program stored in the memory 131.

Of course, instead of the time control there can be a displacement measurement in the drive unit 5 and according to predeterminable positions the described pulses can be generated and distributed. The said switching modules 10, i.e. the 4/2-way-valve 144, the 3/2-way-valves 148, 150 and the restrictor return valves 147, 155 are only examples, and can of course be substituted and/or supplemented according to different control functions by different switching modules 10.

One problem with the individual modes is creating a reference parameter which forms the starting point for joining the individual control modules 9 or displacement units 1. A reference parameter of this kind can for example be the speed of a pneumatic cylinder 13 and thus the cycle time of a displacement unit 1. In this case after the initialisation mode the cycle time of each individual displacement unit 1 can be determined and for example sent into the central control unit 134. There a comparison of all cycle times of the displacement units 1 is performed and the „slowest“ displacement unit 1 is determined, i.e. the greatest pulse time of the displacement unit 1 is established. To this cycle time the cycle times of the other displacement units 1 are coordinated for example by means of the learning mode.

In the jointly described Figs. 10 and 11 the sequence of the initialisation mode is shown in combination with the learning mode for optimising reference valves with respect to the cycle time. If an assembly system is to be composed of several not shown displacement units 1, method step 159 is commenced. In the latter there is a selection of a physical target variable in the central control unit 134 shown in Fig. 7 and/or in the control module 9 to be optimised from a specific number of such physical target variables. The latter can for example be the maximum speed, the minimum impact or the necessary speed. The necessary speed of a displacement unit 1 is oriented to each displacement unit 1 which takes the greatest time for a specific assembly step to be performed thereby for procedural reasons. As this slowest displacement unit 1 determines the cycle time of the entire assembly system it is not necessary that other displacement units 1, which are „faster“ than the „slowest“ displacement unit 1 perform the assembly steps to be performed thereby in their minimum possible individual cycle time.

If the individual cycle times, i.e. the individual speeds of the various displacement units 1 are adjusted to those of the “slowest“ displacement unit 1, in this way unnecessary wear can be

The latter is illustrated in more detail in Fig. 11. The learning mode begins with procedure 164, in which the control module 9 programmed with reference values or the displacement unit 1 is started manually and externally, followed by method step 165. In the latter the switching modules 10 of the displacement unit 1 are actuated according to the entered actual reference values. Once the switching modules 10 have ended their prespecified sequences and thus the displacement unit 1 for example has reached its reference position according to the reference values, in sequence 166 the actual values are detected, i.e. for example the actual positions of the components 3, 4 of the displacement unit 1. Afterwards in procedure 167 a comparison of the detected actual values with the entered reference value is made and where there is insufficient correspondence there is a return to the beginning of method step 165 and thus a further actuation of the switching modules 10 and a change of position of the elements e.g. the components 3, 4 of the displacement unit 1 is performed. If the reference-actual value comparison is successful in procedure 167, i.e. the actual values correspond with the reference values, the actual target variable of the relevant displacement unit 1 are stored in the sequence 168. Which target variable should be stored from a possible number of actual target variables is determined by the selection made in method step 159 of the physical target variable to be optimised.

After completing the learning mode of the individual displacement units 1 in method step 169 it is queried whether the method step 159, the sequence 160, the procedure 161, the method

Said target value can for example, as already indicated, be the pulse time of the „slowest“ displacement unit 1, which determines the necessary speed for all displacement units 1. In procedure 171 beginning with the first displacement unit 1, a comparison of the actual-target variable is made with the target value. If the latter do not correspond method step 172 is performed, which is formed for example by sequence 163 i.e. by the learning mode. After completing the learning mode i.e. after ending sequence 163 and adjusting the actual values of the displacement unit 1 to the target value procedure 171 is carried out, i.e. a comparison of the actual target variable of the first displacement unit 1 with the target value. If these two do not coincide there is a return to the beginning of method step 172, i.e. to the learning mode. If the comparison is successful however, i.e. the latter coincide, it is queried in sequence 173, whether all actual target variables of all displacement units 1 or all control modules 9 have been compared and adjusted by means of procedure 171 with the target value.

It should also be mentioned that method steps 159, 162, 165, 169, 172 and/or sequences 160, 163, 168, 170 and/or procedures 161, 164, 167, 170 can be preset in the central control unit 134 and in an individual control module 9 of a displacement unit 1 or in several control modules 9 and several displacement units 1.

In the jointly described Figs. 12 and 13 a further embodiment of the displacement unit 1 according to the invention is shown. The latter is basically the same as the displacement unit 1 shown in Figs. 4 and 5. The displacement unit 1 comprises adjacent to the outer surface 41 signalling and/or monitoring members 16 and switching modules 10. The signalling and/or monitoring members 16, which can have separate control modules 9 and/or logic elements 139, preferably have contacting openings 175 arranged symmetrically about the central plane 106, which forms a line connection to a bus line 136, comprising for example two individual conductors 176, which forms the electric distribution bus bar 72. The bus line 136 can however also be designed as a 3-conductor system, one conductor of which is designed as an emergency off conductor by means of which the power supply of all actuators 138 is interrupted. In this case the signalling and/or monitoring member 16 comprises for example an initiator element 177, an electronic module 178 forming a logic element 139 connecting the latter and connecting lines 179 from the electronic module 178 to the contacting openings 175 via which the received signals are transmitted from the initiator element 177 to the bus line 136.

The switching modules 10 also do not have the shown contacting openings 175 by which the latter are supplied with power via the bus line 136. The bus line 136 has for example a circular cross section, whereby it is possible to change both the switching modules 10 and the signalling and/or monitoring members 16, in particular their position as desired along the displacement unit 1. It is also possible however to integrate the bus line 136 into lines 50, in particular into a pneumatic pipe 51 for the switching modules 10.

Finally, it should be noted that in the embodiments described above individual parts have been enlarged disproportionately in order to improve understanding of the solution of the invention. Furthermore, individual parts of the previously described combinations of features of the individual embodiments can form independent solutions according to the invention in connection with other individual features from other embodiments.

The objectives and solutions relating thereto according to the invention can be taken from the detailed descriptions of these Figures.

List of Reference Numbers

- | | | | |
|-----|-------------------------------------|-----|----------------------------|
| 1. | Displacement unit | 41. | Outer surface |
| 2. | Mounting part | 42. | Console |
| 3. | Component | 43. | 4/2-way-valve |
| 4. | Component | 44. | Restrictor return valve |
| 5. | Drive unit | 45. | Restrictor return valve |
| 6. | Guiding device | 46. | 3/2-way-valve |
| 7. | Control unit | 47. | 3/2-way-valve |
| 8. | Member | 48. | Drive |
| 9. | Control module | 49. | Control line |
| 10. | Switching module | 50. | Line |
| 11. | Pneumatic valve | 51. | Pneumatic pipe |
| 12. | Pneumatic drive | 52. | Input |
| 13. | Pneumatic cylinder | 53. | Bus connector plug |
| 14. | Closing element | 54. | Output |
| 15. | Cylindrical pipe | 55. | Distribution bar |
| 16. | Signalling and/or monitoring member | 56. | Bar length |
| 17. | Proximity switch | 57. | Bar width |
| 18. | Transport device | 58. | Bar height |
| 19. | Drive and/or guiding device | 59. | End face |
| 20. | Workpiece carrier | 60. | Opening |
| 21. | Drive axis | 61. | Channel |
| 22. | Central axis | 62. | Upper side |
| 23. | Drive wheel | 63. | Opening |
| 24. | Distance | 64. | Air inlet channel |
| 25. | Guiding wheel | 65. | Air outlet channel |
| 26. | Surface | 66. | Connecting channel |
| 27. | Flank surface | 67. | Connecting channel |
| 28. | Inner spacing | 68. | Upper side |
| 29. | Recess | 69. | Sound damper |
| 30. | Wheel width | 70. | Underside |
| 31. | Upper side | 71. | Drive |
| 32. | Mount | 72. | Distribution bus bar |
| 33. | Roller | 73. | Coupling device |
| 34. | Bore | 74. | Plug |
| 35. | Bolt | 75. | Display element |
| 36. | Piston | 76. | Display |
| 37. | Piston surface | 77. | Input device |
| 38. | Piston rod | 78. | Keyboard |
| 39. | Pressing piece | 79. | Input and/or output device |
| 40. | Threaded section | 80. | End side face |

- 161. Procedure
- 162. Method step
- 163. Sequence
- 164. Procedure
- 165. Method step

- 166. Sequence
- 167. Procedure
- 168. Sequence
- 169. Method step
- 170. Procedure

- 171. Procedure
- 172. Method step
- 173. Sequence
- 174. Procedure
- 175. Contacting opening

- 176. Individual conductor
- 177. Initiator element
- 178. Electronic module
- 179. Connection line